Eurovent
created with passion

CE
13

Declaration of Performance

According to Annex III of Regulation (EU) No. 305/2011
Nr. DoP – NoPB/0009/13/001
for the product

Eurovent GEO 20 GARDEN

1. Unique identification code of the product type:	Eurovent GEO 20 GARDEN, nr NoPB/0009/13/001, accord. to. DIN EN 13252:2000/A1 : 2005
2. Type batch or serial number or any other element allowing identification of the construction product as required und article 11(4)	Example + (lot nr. see packaging)
3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Geomembrane made of high density polyethylene (HDPE) made especially for vertical and horizontal drainage to ventilate and drain.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required und article 11(2)	Eurosystem Polska Sp. z o.o. Wiejska 13, 46-055 Przywory, Polska VAT PL 9372516153
5. Contact address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2)	not relevant
6. AVCP: System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	2+
7. Notified body: In case of declaration of performance concerning a construction product covered by a harmonised standard	Notified factory production control Nr. 0799 Kiwa MPA Bautest GmbH, TBU Greven performed the initial inspection of the manufacturing and of factory production control and issued the certificate of conformity of the production control: 0799-CPD-117.

Eurovent
created with passion

8. Declared performance

Essential characteristics	Performance		Harmonized technical specification
	Units	Values	
Reaction to fire	class	E	EN 13501-1
Elongation MD	[%]	> 22	EN 12311-2
Elongation CMD	[%]	> 12	EN 12311-2
Resistance to impact	[mm]	> 380	EN 12691
Tensile strength MD	[N/mm]	302/50	EN 12311-2
Tensile strength CMD	[N/mm]	308/50	EN 12311-2
Tearing resistance MD	[N]	257	EN 12310-1
Tearing resistance CMD	[N]	224	EN 12310-1
Water storage capacity	[l/m²]	ca. 7,0	internal method

9. Declaration: the performance of the product is in conformity with the declared performance in point 9. This declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Przywory, 17.06.2013

Marcin Świerta
President



Eurosystem Polska Sp. z o.o.
ul. Wiejska 13, 46-055 Przywory, Poland